



Pica sto sa frižiderom i fiokama (Ventilatorsko hlađenje)



Pica sto sa frižiderom i fiokama (Ventilatorsko hlađenje)

- Kapacitet fioke : GN 1/1 1500 mm.
- Radna temperatura; 0° C , + 5° C (na sobnoj temperaturi. 43° C) - 220 V-230 V -1 +N
- 50 60 Hz snaga. - "CFC Free" , R-134 A gasno punjenje.
- 40 kg/m3 gustina.
- Elektronska kontrola temperature i odmrzavanja sa prikazom.
- Automatsko isparavanje vode tokom odmrzavanja.
- Izmenjiva klima.
- Ventilatorsko hlađenje.
- "Ozone-friendly" 48 mm debljina poliuretanske izolacije.
- Samozatvarajuća vrata .
- Zaobljeni prednji gornji rubovi.
- Isparivač od bakarnih cevi sa aluminijumskim perajem.
- Podesivo, kućište od nerđajućeg čelika, police presvučene plastikom.
- Telo od nerđajućeg čelika.



Šifra	Opis	Dimenzije mm			Težina kg	m ³	Snaga kw	Kapacitet lt	Cena Euro
		a	b	c					
PIN150.70.01-2C	Pica stol, 2 Fioke+1 vrata (Sa ventilatorom)	1500x700x850			95	0.9	0.35	300	1.925
PIN150.70.01-4C	Pica sto, 4 Fioke	1500x700x850			95	0.9	0.35	300	2.325
PIN200.70.01-2C	Pica sto, 2 Fioke+2 vrata (Sa ventilatorom)	2000x700x850			120	1.2	0.35	500	2.180
PIN200.70.01-4C	Pica sto, 4 Fioke+1 vrata (Sa ventilatorom)	2000x700x850			120	1.2	0.35	500	2.575
PIN200.70.01-6C	Pica sto 6 Fioka	2000x700x850			120	1.2	0.35	500	2.975
PIN255.70.01-2C	Pica sto, 2 Fioke + 3 vrata (Sa ventilatorom)	2550x700x850			145	1.5	0.50	700	2.680
PIN255.70.01-4C	Pica sto, 4 Fioke + 2 vrata (Sa ventilatorom)	2550x700x850			145	1.5	0.50	700	3.100
PIN255.70.01-6C	Pica sto, 6 Fioka + 1 vrata (Sa ventilatorom)	2550x700x850			145	1.5	0.50	700	3.400
PIN255.70.01-8C	Pica sto 8 Fioka	2550x700x850			145	1.5	0.50	700	3.800